

Akcijski katalog

01.03.2024

Slika	Naziv/Model	Proizvod aC	VPC	MPC
	Integrated Mount Tester PFM906-EP > Supports IPC, HDCVI, AHD, HDTVI, CVBS and SDI monitor video display. > HDMI input and output. > 12 VDC 2A and USB 5V 2A output. > 7-in 1080p HD full-angle retina capacitive IPS touchscreen. > TDR network cable test and cable tracker function. > Optical power meter function.		80682	96818.40
			59380	71256.00
	Access Standalone ASI2201H-W > PC + ABS, suitable for indoor and outdoor use. > 2.4" LCD screen with a resolution of 240 × 320. > Operating temperature: -30 °C to +65 °C (-22 °F to +149 °F). > IP65 rated (silicone sealant is needed, see Quick Start Guide). > Option to switch between reader and controller mode for added convenience. > 30,000 users, 30,000 cards, 30,000 passwords, 50 admin accounts, and 150,000 records. > Card/remote/password unlock and unlock through their combinations. > IC card, ID card and NFC technology. > Brand-new design with a slim, elegant structure. > Supports access control security module expansion to avoid tampering, increasing access safety. > Supports duress alarm, tamper alarm, intrusion alarm, door contact timeout alarm, illegal card exceeding threshold alarm, illegal password exceeding threshold alarm and external alarm. > Supports guest users, patrol users, blocklist users, VIP users, general users, and others. > TCP/IP and Wi-Fi communication; auto registration, P2P registration, and DHCP. > Supports PC/mobile web client. > Supports online update and USB update. > Doorbell function. > Audio prompts. > Compatible with SmartPSS-AC and DSS Pro.		25228.00	30273.60
			12110.00	14532.00
	RG59 bez napajanja 100m		2050.00	2460.00
	HAC-HDW1800M + DOZNA PFA13A-E 4K Real-time HDCVI IR Eyeball Camera > Max. 4K resolution, real-time video transmission > CVI/CVBS/AHD/TVI switchable > Fixed lens (2.8mm; 3.6mm; 6mm optional) > Max. IR length 30m, Smart IR > IP67, 12V±30%DC		3930.00	4716.00
	PFM920I-6UN-C UTP CAT6 Cable > 305 m (1000 ft)/carton UTP CAT6, power over Ethernet, compatible with one cable > High-purity oxygen-free copper conductor > Customized PVC outer sheath; CE CPR Eca flame retardant class certified > 10-year warranty		10996.00	13195.20



ASI7213X-T1

Face Recognition Access Controller

- > 2.5D curved screen
- > 7-inch LCD display with resolution of 1024 × 600
- > 2MP CMOS, WDR
- > Auto illumination reduces light pollution
- > Can hold 100,000 users, 100,000 face images, 100,000 cards, 100,000 password, 50 administrators, and 300,000 records
- > Support face, IC card, password unlock and unlock through their combinations
- > With face detection box; the largest face among faces that appear at the same time is recognized first; the maximum face size can be configured on the web
- > Face-camera distance: 0.3 m–2.0 m; human height: 0.9 m–2.4 m (lens-ground distance: 1.4 m)
- > With face recognition algorithm, the terminal can recognize more than 360 positions on human face
- > Face recognition speed: 0.2 s per face
- > Support liveness detection
- > Accurate recognition in backlight and front light
- > Various unlock status display modes protect user privacy

133500.00 160200.00



ASI1212D

Fingerprint Standalone

- > Touch keyboard and LCD display
- > Support 30,000 valid cards & 150,000 records
- > Support multiple cards(default IC card) ("D" means ID EM card)
- > Support card, password, fingerprint and combination
- > TCP/IP to PC
- > Support P2P add device
- > Wiegand or RS-485 interface to reader
- > Door time out alarm, intrusion alarm, duress alarm and tamper alarm
- > Anti-passback, multi-card open
- > Support 128 efficient time and holiday schedules
- > USB import/export configuration or log file;

13670.00 16404.00