



## SD49425XB-HNR

### 4MP 25x Starlight IR WizSense Network PTZ Camera

- > 1/2.8" 4Megapixel CMOS
- > Powerful 25x optical zoom
- > Starlight technology
- > Max.25/30fps@4M
- > Perimeter protection
- > Support PoE+
- > IR distance up to 100m
- > SMD PLUS
- > IP66

**49 580,00 sa pdv**



## VTH2421FB(W)-P

### IP Indoor Monitor

- > 7" TFT Capacitive touch screen, 1024 x 600
- > IPC surveillance
- > Alarm integration> High performance & Cost-effective
- > Embedded 8GB SD card
- > Support standard PoE

**15 274,00 sa pdv**



## HAC-EW2501P

### 5MP HDCVI IR-Fisheye Camera

- > 1/2.8" 5Megapixel progressive scan CMOS
- > Panoramic fisheye lens
- > Max. 20fps@5MP
- > Built-in Mic
- > 120db true WDR, Starlight, 2D&3D NR
- > Max. IR length 10m, Smart IR
- > DC12V

**16 290,00 sa pdv**



**2 459,00 sa pdv**

**RG59 bez napajanja 100m**



DOZNA [PFA13A-E](#)

## HAC-HDW1800M

### 4K Real-time HDCVI IR Eyeball Camera

- > Max. 4K resolution, real-time video transmission
- > CVI/CVBS/AHD/TVI switchable
- > Fixed lens (2.8mm; 3.6mm; 6mm optional)
- > Max. IR length 30m, Smart IR
- > IP67, 12V±30%DC

**4 715,00 sa pdv cena sa doznom**



## VTO2202F-P-S2

### 2-wire IP Villa Door Station

- > Anodized aluminum front panel.
- > CMOS low illumination 2MP HD colorful 160° fisheye camera.
- > Video intercom function.
- > Access control function that supports two locks.
- > Mobile phone app, talk to the visitor or unlock the door remotely on your phone.
- > Compatible with 2-wire interface & RJ45 interface.
- > IK07&IP65.
- > Support H.265.
- > Support surface and flush mount.
- > PoE.

**14 930,00 sa pdv**



## PFM920I-6UN-C

### UTP CAT6 Cable

- > 305 m (1000 ft)/carton UTP CAT6, power over Ethernet, compatible with one cable
- > High-purity oxygen-free copper conductor
- > Customized PVC outer sheath; CE CPR Eca flame retardant class certified
- > 10-year warranty

**14 395,00 sa pdv**



## ASI7213X-T1

**160 220,00 sa pdv**

Face Recognition Access Controller

- > 2.5D curved screen
- > 7-inch LCD display with resolution of 1024 × 600
- > 2MP CMOS, WDR
- > Auto illumination reduces light pollution
- > Can hold 100,000 users, 100,000 face images, 100,000 cards, 100,000 password, 50 administrators, and 300,000 records
- > Support face, IC card, password unlock and unlock through their combinations
- > With face detection box; the largest face among faces that appear at the same time is recognized first; the maximum face size can be configured on the web
- > Face-camera distance: 0.3 m–2.0 m; human height: 0.9 m–2.4 m (lens-ground distance: 1.4 m)

- > With face recognition algorithm, the terminal can recognize more than 360 positions on human face
- > Face recognition speed: 0.2 s per face
- > Support liveness detection
- > Accurate recognition in backlight and front light
- > Various unlock status display modes protect user privacy
- > Support enabling/disabling the temperature monitoring mode; temperature monitoring range is 30°C to 45°C; temperature monitoring distance range is 0.3 m–1.8 m; temperature monitoring error is  $\leq 0.5^{\circ}\text{C}$ ; report temperature anomaly alarm
- > Support mask detection, report alarm of abnormal events without wearing a mask
- > Support duress alarm, tamper alarm, intrusion alarm, door contact timeout alarm, and illegal card exceeding threshold alarm
- > Support general users, patrol users, VIP users, guest users, and special users



## ASI1212D

### Fingerprint Standalone

- > Touch keyboard and LCD display
- > Support 30,000 valid cards & 150,000 records
- > Support multiple cards(default IC card) (“-D” means ID EM card)
- > Support card, password, fingerprint and combination
- > TCP/IP to PC
- > Support P2P add device
- > Wiegand or RS-485 interface to reader
- > Door time out alarm, intrusion alarm, duress alarm and tamper alarm
- > Anti-passback, multi-card open
- > Support 128 efficient time and holiday schedules
- > USB import/export configuration or log file;

**16 400,00 sa pdv**