IP Products

DHI-VTO2101E-P-S2



HD CMOS camera.
Zinc alloy panel, IP65 and IK10 rated.
ICR night vision and voice prompt.
Video and audio messaging.
TCP/IP, and SIP.
Surface mounted.

230.00 276.00

89.00

241.00

289.00

498.00

346.80

597.60

289.20

106.80

DHI-VTO2311R-WP

DHI-VTO3311Q-WP



Ultra slim design.

PC and ABS material make it ideal for indoor and outdoor use.

1/2.8" 2-MP HD CMOS camera.

Offers two-way video call with indoor monitors.

Video and voice messages from visitors can be checked on the indoor

monitor.

Video call and unlocking through app.

IR illumination and auto WDR.

Wi-Fi connection.

IP65 rated.

H.264 and H.265.

Unlock with IC card.

PoE power supply.

Full metal casing design. Included rain cover.

Customizable Number of Buttons.

Optional red-brown or dark blue front cover. (red-brown P/N:

1.1.03.15.10221, dark blue P/N: 1.1.03.15.10220)

1/2.8" 2-MP HD CMOS camera.

Offers two-way video call with indoor monitors.

IR illumination and auto WDR.

Supports two locks.

Voice call and unlocking through app.

IK08 and IP65 rated. H.264 and H.265.

Unlock with IC card.

Wi-Fi connection.

PoE power supply.

Included rain cover.

Full metal casing design.

Customizable Number of Buttons.

Optional red-brown or dark blue front cover. (red-brown P/N:

1.1.03.15.10221, dark blue P/N: 1.1.03.15.10220)

1/2.8" 2-MP HD CMOS camera.

Offers two-way video call with indoor monitors.

IR illumination and auto WDR.

Supports two locks.

Voice call and unlocking through app.

Two wires and RJ-45 connection.

 $\ensuremath{\mathsf{IK08}}$ and $\ensuremath{\mathsf{IP65}}$ rated.

H.264 and H.265.

Unlock with IC card. PoE power supply.

DHI-VTO6521K

DHI-VTO3312Q-P



 $\hbox{4.3-inch LCD display with easy-to-press metal buttons.}\\$

 $\hbox{2-MP low-illumination HD Starlight image sensor.}\\$

Auto illumination.

Full duplex communication.

All-in-one management platform and voice call through app.

Multiple verification methods: Password, IC card, QR code, and remote

unlocking.

Surface mount and flush mount support.

IP65 rated with support for outdoor installation.

DHI-VTH2621G-P	7" TFT capacitive touch screen, 1024 × 600. 6-channel alarm input and 1-channel alarm output. Standard PoE. Supports the outdoor station and IPC monitor. H.265 and H.264 video coding. Customize DND mode and the effective period. High-performance and cost-effective.	150.00	180.00
DHI-VTH2621GW-P	7" TFT capacitive touch screen, 1024 × 600. 6-channel alarm input and 1-channel alarm output. Standard PoE. Supports the outdoor station and IPC monitor. H.265 and H.264 video decoding. Customize DND mode and the effective period. High-performance and cost-effective.	150.00	180.00
DHI-VTH2621G-WP	7" TFT capacitive touch screen, 1024 × 600. 6-channel alarm input and 1-channel alarm output. Wi-Fi. Standard PoE. Supports the outdoor station and IPC monitor. H.265 and H.264 video decoding. Customize DND mode and the effective period. High-performance and cost-effective.	159.00	190.80
DHI-VTH2621GW-WP	7" TFT capacitive touch screen, 1024 × 600. 6-channel alarm input and 1-channel alarm output. Wi-Fi. Standard PoE. Supports the outdoor station and IPC monitor. H.265 and H.264 video decoding. Customize DND mode and the effective period. High-performance and cost-effective.	159.00	190.80
DHI-VTH2622G-W	7" TFT capacitive touch screen, 1024 × 600. 6-channel alarm input and 1-channel alarm output. Wi-Fi. Supports the outdoor station and IPC monitor. H.265 and H.264 video decoding. 2-wire digital communication. Customize DND mode and the effective period. High-performance and cost-effective.	194.00	232.80
DHI-VTH2622GW-W	7" TFT capacitive touch screen, 1024 × 600. 6-channel alarm input and 1-channel alarm output. Wi-Fi. Supports the outdoor station and IPC monitor. H.265 and H.264 video decoding. 2-wire digital communication. Customize DND mode and the effective period. High-performance and cost-effective.	194.00	232.80
DHI-VTO2202F-P-S2	Anodized alumimum front panel CMOS low illumination 2MP HD colorful 160° fisheye camera Video intercom function Access control function, support two locks Mobile phone app, talk to the visitor or unlock the door remotely on your phone Compatibile with 2-wire interface & RJ-45 interface IKO7 & IP65 Support surface and flush mount Support H.265 PoE	242.00	290.40



Anodized alumimum front panel

CMOS low illumination 2MP HD colorful 160° fisheye camera

Video intercom function

Access control function, support two locks

Mobile phone app, talk to the visitor or unlock the door remotely on your

phone

Compatibile with 2-wire interface & RJ-45 interface

IK07 & IP65

Support surface and flush mount

Support H.265

PoE

196.00 235.20

263.00

479.00

1072.00 1286.40

250.00

250.00

300.00

300.00

315.60

574.80

DHI-VTO4202FB-P-S2

DHI-VTO4202F-P-S2

 $\cdot \, \text{Anodized alumimum front panel} \,$

- · CMOS low illumination 2MP HD colorful 160° fisheye camera
- · Video intercom function
- · Access control function that supports two locks
- · Uses a smartphone app to talk to visitors or unlock the door remotely on your phone
- \cdot Compatible with 2-wire interface & RJ45 interface
- · IK07&IP65
- · Supports H.265 encoding
- · Support surface and flush mount
- · Expandable functions with various modules

DHI-VTO6521F



4.3 inch IPS display, aluminum anode housing, metal button;

2MP low illumination, high definition, and star light image sensor;

auto illumination;

full duplex communication;

support management platform and voice call through app;

 $multiple\ verification\ methods: password,\ IC\ card,\ and\ remote\ unlock;$

Surface mount or flush mount;

IP 65 (silicone sealant is needed, see the quick start guide), installed

outdoors

DHI-VTO7541G-S2



8-Inch HD capacitive display;

2MP HD Dual cameras and starlight image sensor;

Auto illumination and night vision;

Two-way voice call;

Supports platform management and audio from smartphone application;

Supports password/IC card/remote/fingerprint/QR code/Face unlock;

With algorithm developed by Dahua, the VTO supports 20000 allowlist face images; 1:N face recognition time is 0.3 s/person; the recognition distance

can be configured to 0.3 m-2 m;

Supports liveness detection;

 $\label{lem:capacitive finger print} Capacitive finger print recognition and stores \ 10,000 \ finger prints;$

Supports card swiping area indicator;

Supports flush mount and surface mount;

Suitable for outdoor use with IP65 rated.

DHI-VTH5422HW



- \cdot 7" TFT capacitive touch screen
- \cdot 6-channel alarm input and 1-channel alarm output
- $\cdot \, \text{Supports standard PoE} \,$
- \cdot Supports H.265 and H.264 video coding
- $\cdot \, \text{Supports 2-wire digital communication} \\$
- $\cdot \ \text{Power over two-wire switch} \\$
- \cdot Call management center with one tap
- $\cdot \, \text{Supports daisy chain topology} \\$
- · 2.5D screen glass

DHI-VTH5422HB



- · 7" TFT capacitive touch screen
- \cdot 6-channel alarm input and 1-channel alarm output
- · Supports standard PoE
- · Supports H.265 and H.264 video coding
- · Supports 2-wire digital communication
- $\cdot \ \text{Power over two-wire switch} \\$
- · Call management center with one tap
- $\cdot \, \text{Supports daisy chain topology} \\$
- $\cdot\, 2.5 D \text{ screen glass}$

DHI-VTH5421HW		TFT capacitive touch screen 6-channel alarm input and 1-channel alarm output Supports standard POE Supports H.265 and H.264 video coding 2.5D screen glass	268.00	321.60
DHI-VTH5421HB		TFT capacitive touch screen 6-channel alarm input and 1-channel alarm output Supports standard POE Supports H.265 and H.264 video coding 2.5D screen glass	268.00	321.60
DHI-VTH2421FW-P	1 1 7 S	7" TFT 1024×600, Capacitive IPC surveillance Alarm integration (6/1) Standard POE Enbedded 8GB SD card	191.00	229.20
DHI-VTH2421FB-P	**************************************	7" TFT 1024×600, Capacitive IPC surveillance Alarm integration (6/1) Standard POE Enbedded 8GB SD card	191.00	229.20
DHI-VTS5340B		10 inch glass touch screen; resolution 1024×600. Remote unlock through management station when watching videos captured by door stations or during calls with door stations Support two-way voice call with door stations and indoor monitors. Support videos from four channels (VTO and IPC). Support SD expansion, videos and snapshots captured during video calls with door stations. Two audio input modes: Handsfree and handset. Installed on the desk; bracket angle range 0–45°. Support HDMI output; max. resolution 1024×600.	638.00	765.60
DHI-VTO3221E-P		2MP CMOS camera, H:140° Aluminum panel, IP55,IK08 Night vision&Voice indication Group call Video & Audio messaging Remote intercom with mobile APP(DMSS) Surface mounted	363.00	435.60
DHI-VTO2202F-P		2MP CMOS camera Mechanical button Night vision & voice indicator PoE 160° angle of view Compatible with VTH5222CH-S1 and VTNS1006A-2 Group call Power supply by 2-wire Aluminium alloy plate IP55&IK07 Surface mounted and flush mounted With namepalte	254.00	304.80
DHI-VTO3211D-P1-S2		 Metal casing; IR illumination and night vision; Two-way audio; Platform management and voice call through app; Card unlock, app unlock, and indoor monitor unlock; IP65 (silicone sealant is needed, see the quick start guide) and IK08. 	205.00	246.00



205.00 246.00

276.00

286.80

202.80

168.00

DHI-VTO4202F-MB1



" 1 buttons Anodized front alumimum panel, IP65, IK07 One button to call user directly "

35.00 42.00

DHI-VTO4202F-MB2



" 2 buttons Anodized front alumimum panel, IP65, IK07 One button to call user directly "

40.00 48.00

DHI-VTO4202F-MB5		" 5 buttons Anodized front alumimum panel, IP65, IK07 One button to call user directly "	51.00	61.20
DHI-VTO4202F-MK	国 漢 王 绍 区 湖 丛 河 区 土 鎮 区	" Unlock by password Metal backlight keyboard Anodized front alumimum panel, IP65, IK07 "	108.00	129.60
DHI-VTO4202F-MF		" Unlock by fingerprint Anodized front alumimum panel, IP65, IK07 "	141.00	169.20
DHI-VTO4202F-ML		" Show three status Anodized front alumimum panel, IP65, IK07 "	35.00	42.00
DHI-VTO4202F-MS		" 3.0 inch STN display Anodized front alumimum panel, IP65, IK07 "	51.00	61.20
DHI-VTO4202F-MR		" Local card openning(Mifare card) Anodized front alumimum panel, IP65, IK07 "	40.00	48.00
DHI-VTO4202F-MN		Blank ModuleIK07;IP65	19.00	22.80
DHI-VTO4202F-MR1			40.00	48.00
DHI-VTO4202FB-MB1	- 0	One-button module	41.00	49.20



DHI-VTO4202FB-MR1



ID card swiping module

40.00

48.00

DHI-VTO7521G-S2



8-Inch HD capacitive display;

2MP HD Dual cameras and starlight image sensor;

Auto illumination and night vision;

Two-way voice call;

Supports platform management and audio from smartphone application;

Supports password/IC card/remote/QR code unlock;

Supports card swiping area indicator;

Supports flush/surface mount;

Suitable for outdoor use with IP65 rated.

900.00 1080.00

688.00

487.00

381.00

584.40

457.20

825.60

DHI-VTO6541H



4.3 inch IPS display, touch button;

2MP low illumination, high definition, and star light image sensor;

support auto illumination and night vision;

full duplex communication;

support management platform and voice call through app;

multiple verification methods: password, IC card, remoteand face unlock; algorithm developed by Dahua ensures the door station support 10,000

face comparison speed 0.2S/person, adjustable face recognition range

0.3m-2m:

whitelist face images;

support liveness detection;

Surface mount or flush mount;

IP 65 (silicone sealant is needed, see the quick start guide), installed

outdoors

DHI-VTO6531H



4.3 inch IPS display, touch button;

2MP low illumination, high definition, and star light image sensor;

support auto illumination and night vision;

full duplex communication;

support management platform and voice call through app;

multiple verification methods: password, IC card, remote and face unlock,;

algorithm developed by Dahua ensures the door station support 10,000

whitelist face images;

face comparison speed 0.2S/person, adjustable face recognition range

0.3m-2m;

support liveness detection;

Surface mount or flush mount;

IP 65 (silicone sealant is needed, see the quick start guide), installed

outdoors

DHI-VTO6521H



4.3 inch IPS display, touch button;

2MP low illumination, high definition, and star light image sensor;

full duplex communication;

support management platform and voice call through app;

multiple verification methods: password, IC card, and remote unlock;

Surface mount or flush mount;

IP 65 (silicone sealant is needed, see the quick start guide), installed

outdoors

4.3 inch IPS display, touch button;

2MP low illumination, high definition, and star light image sensor;

auto illumination;

full duplex communication;

support management platform and voice call through app;

 $\ \ \, \text{multiple verification methods: password, ID card, and remote unlock;}$

Surface mount or flush mount; IP 65 (silicone sealant is needed, see the quick start guide), installed

outdoors

381.00

457.20

DHI-VTO6521H-D



2MP CMOS camera,H:140° 2.3' OLED Aluminum Door released by card/password SIP protocal

387.00 464.40

DHI-VTO1210C-X-S1

DHI-VTO6221E-P



" 1.3MP CMOS camera, H:75° $3^{\prime\prime\prime}$ STN LCD screen, phonebook Stainless steel panel, IP54,IK07 Night vision & Approaching induction Local card openning(Mifare card,13.56MHz) Group call Video & Audio messaging Surface mounted(VTOB110)& Flush mounted(VTOB103) "

414.00 496.80

DHI-VTH5321GW-W



Android More user-friendly UI Ethernet and Wi-Fi 7" TFT capactive touch screen,1024×600 Micro SD card optional, MAX 256GB Quick configuration for villa system.

237.00 284.40

DHI-VTH5321GB-W



Android More user-friendly UI Ethernet and Wi-Fi 7" TFT capactive touch screen,1024×600 Micro SD card optional, MAX 256GB $\label{eq:Quick configuration for villa system.}$

237.00 284.40

DHI-VTH5421E-H



The 7 inch handset indoor monitor has 8 alarm input ports. Users can talk to visitors through the indoor monitor and watch videos captured by outdoor stations. It is applicable to residential areas, hotels, governments, schools, factories,

248.00 297.60

DHI-VTH5421EW-H



The 7 inch handset indoor monitor has 8 alarm input ports.

Users can talk to visitors through the indoor monitor and watch videos $% \left\{ \left(1\right) \right\} =\left\{ \left(1\right) \right$ captured by outdoor stations. It is applicable to residential areas, hotels, governments, schools, factories,

248.00 297.60

and more.

and more.

DHI-VTH5341G-W



Android More user-friendly UI 4-core processor Ethernet and Wi-Fi 10" TFT capactive touch screen,1024×600 Micro SD card optional, MAX 256GB

370.00 444.00

DHI-VTH5221D-S2



" 7"" TFT Capacitive touch screen(Black)

IPC surveillance

6ch wired alarm integration, 6ch wireless alarm integration(433MHZ) Micro SD card optional, max 32GB

Record & Snapshot(SD card needed)

Surface mounted "

248.00 297.60 DHI-VTH5221DW-S2



" 7"" TFT Capacitive touch screen(white)
IPC surveillance
6ch wired alarm integration, 6ch wireless alarm integration(433MHZ)
Micro SD card optional, max 32GB
Record & Snapshot(SD card needed)
Surface mounted "

260.00 312.00

Analog Products

DHI-VTH1020J



- \cdot 7" TFT screen
- \cdot Video intercom function: Unlock, voice call, video call and volume adjustment
- · Mechanical button
- $\cdot \, \text{Multiple bell sounds}$

95.00 114.00

DHI-VTH1020J-T



- · 7" TFT screen
- \cdot Video intercom function: Unlock, voice call, video call and volume adjustment
- $\cdot \, \mathsf{Touch} \; \mathsf{button} \\$
- · Multiple bell sounds
- · Take snapshots

133.00 159.60

Kits

DHI-KTA02

DHI-KTP02



- · 7" TFT screen
- · Video intercom function: Unlock, voice call, video call, volume adjustment
- · Quantity of video intercom: 2 door stations + 3 indoor monitors
- · Multiple bell sounds
- · Supports digital wide dynamic range (DWDR)

135.00 162.00

IP Villa Door Station

- > High definition camera; WDR
- > Operating temperature -30°C to 60°C
- > IP65(Silicone sealant is needed. For details, see the quick start guide.)
- > Supports auto IR illumination and D/N
- > Card/app remote/indoor monitor unlock
- > Supports two-way voice call; support calls between door stations and app
- > 10,000 cards
- > Tamper Alarm
- > Support standard PoE power supply

355.00 426.00

- > Control two locks
- IP Indoor Monitor
- > IPC surveillance
- > Alarm integration
- > High performance
- > Embeded 8GB SD card
- > Support standard PoE
- > Quick configuration without computers

DHI-KTP01(F)

DHI-KTP01(S)





2MP CMOS camera, H:160°Night vision & Voice indicationAnti-tamper alarmIP55&IK07Video & Audio messaging2-Wire Inteface7-inch TFT $screen IPC\ surveillance Alarm\ integration 2-door\ control Remote\ intercom$ with mobile APP(DMSS)

510.00 612.00

510.00

612.00





ZIVIP CIVIOS camera, H:160 Night vision & Voice indication

Anti-tamper alarm

IP55&IK07

Video & Audio messaging

2-Wire Inteface

7-inch TFT screen

IPC surveillance Alarm integration

2-door control

Remote intercom with mobile APP(DMSS)"

IP Villa Door Station

Anodized front alumimum panel

2MP colorful CMOS HD camera with optimized performance under low

illumination

Access control function, Support for two locks

Supports remotely unlock doors by using the smartphone app

IK07&IP65

Supports flush mounting PoE

DHI-KTP04(F)



557.00 668.40

IP Indoor Monitor

7" TFT capacitive touch screen

6-channel alarm input and 1-channel alarm output

Supports standard PoE

H.265 video coding (H.264 by default)

SOS alarm

Supports daisy chain topology

2.5D screen glass

IP Villa Door Station

Anodized front alumimum panel

2MP colorful CMOS HD camera with optimized performance under low

illumination

Access control function, Support for two locks

Supports remotely unlock doors by using the smartphone app

IK07&IP65

Supports surface mounting

PoE

557.00 668.40

439.00

526.80

1 4 4 4 1 1 E

7" TFT capacitive touch screen

6-channel alarm input and 1-channel alarm output

Supports standard PoE

H.265 video coding (H.264 by default)

2.5D screen glass

IP Indoor Monitor

DHI-KTW01



1.Thin lightweight design;

- 2. IR illumination and night vision;
- 3. Two-way audio;
- 4. Platform management and voice call through app;
- 5. Card unlock, app unlock, and indoor monitor unlock;
- 6. IP65 (silicone sealant is needed, see the quick start guide).
- 7. Support wireless network.

DHI-KTP04(S)

IP Villa 2-wire Door Station

Anodized front alumimum panel

 $2\mbox{MP}$ colorful CMOS HD camera with optimized performance under low

illumination

H.265 video incoding (H.264 by default)

Access control function, Support for two locks

Supports remotely unlock doors by using the smartphone app

Compatibility 2-wire Interface & RJ45 Interface

IK07&IP65

Supports flush mounting

Supports standard PoE OR Power over 2-wire switch

639.00 766.80

DHI-KTD01(F)



IP Indoor Monitor

7" TFT capacitive touch screen

6-channel alarm input and 1-channel alarm output Supports standard PoE OR Power over 2-wire switch

H.265 video coding (H.264 by default)

Supports 2-wire digital communication

Supports daisy chain topology

2.5D screen glass

IP Villa 2-wire Door Station
Anodized front alumimum panel

2MP colorful CMOS HD camera with optimized performance under low

illumination

H.265 video incoding (H.264 by default)

Access control function, Support for two locks

Supports remotely unlock doors by using the smartphone app

Compatibility 2-wire Interface & RJ45 Interface

IK07&IP65

Supports surface mounting

Supports standard PoE OR Power over 2-wire switch

639.00 766.80

DHI-KTD01(S)



IP Indoor Monitor

7" TFT capacitive touch screen

6-channel alarm input and 1-channel alarm output Supports standard PoE OR Power over two-wire switch

 $\hbox{H.265 video coding (H.264 by default)} \\$

Supports 2-wire digital communication

Supports daisy chain topology

2.5D screen glass

DHI-KTA03



- \cdot Video intercom function: Unlock, voice call, video call and volume adjustment
- Multiple bell sounds
 Supports digital wide dynamic range (DWDR)
- · Take snapshots

180.00 216.00

		Accessories		
DHI-VTNS1001B-2	****	Supports guide rail mount and wall mount.	114.00	136.80
DHI-VTNS1001B-2-A	pro Pro	Supports guide rail mount and wall mount.	134.00	160.80
DHI-VTNS2003B-2	~	Supports 10-level cascade through the 2-wire port. Supports connecting to 20 devices. Supports guide rail mount and wall mount.	119.00	142.80
DHI-VTM58	• <u>•</u> ••	Accessories of Villa Door Station (Casing+ rain cover+ button cap + screw hole sticker)-red brown	25.00	30.00
DHI-VTM57	• <u>•</u> •	Accessories of Villa Door Station (Casing+ rain cover+ button cap + screw hole sticker)-dark blue	25.00	30.00
DHI-VTM123		· Size: 190mm*100mm*54mm · Dip angle: 45° · Desktop mounted bracket for indoor monitor	19.00	22.80
DHI-DEE1010B		RS485 convertor Used to connect with second lock DC12V. Max 1W	42.00	50.40

DC12V, Max 1W